

IPTZ-P400-10X-V2

2MP 10X OPTICAL ZOOM IR MINI PTZ CAMERA

1080P

- Full 1080P/2MP Recordings

3DNR

- Noise Reduction

UP TO 80M
IR RANGE

80M IR Range


 Pan Range
0° to 250°

 Discrete
size
Only
9.4cm
high

 Tilt Range
-10° to 55°

Image Sensor	1/2.8" Sony Exmor CMOS Sensor
Resolution	1080P (1920X1080)
Min. illumination	0.01lux@(F1.6,AGC ON), 0 Lux with IR
Lens	5.1-51mm
IRIS	F1.6-F22, Auto Iris
Optical/ Digital Zoom	10x Optical Zoom 16X Digital Zoom
Electronic Shutter	1/25s ~ 1/100000s
Day/Night	ICR
Audio compression	G.711-U law
	AWB, AGC Adjustable
Image Settings	Exposure Mode (Auto/Iris Priority/Shutter Priority/Manual) Sharpness, Saturation, Brightness and Contrast Adjustable
WDR Range	Digital WDR
Noise Reduction	2D/3D-DNR
Image Orientation	Mirror/Flip
Privacy Zone	Yes
Motion Detection	Yes
Main Chip	Ambarella S2LM
Video Compression	H.264
Resolution	50HZ:25fps(1920x1080) 60HZ:30fps(1920x1080)
Bit rate	32kbps-16Mbps
Encode Mode	VBR/CBR
Image Quality	Five levels under VBR; Free adjustment under CBR
IP Rating	IP66
Bracket	Wall Bracket
Dimensions	225mm x 165mm x 94mm (L x W x H)
Weight(gross)	920g
IR Distance	80M
Pan Rotation Range	0°-250°
Tilt Rotation Range	-10°-55°
Pan Speed	0.5°-15°/s
Tilt Speed	0.5°-10°/s
Preset Position	256
Network	RJ45
IP Rating	IP66
Power	DC 12V
Remote Monitoring	IE Browsing, CMS 3 Control Software
User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
ONVIF	Support
Ethernet	100Mbps
Power Supply	DC12V
Work Environment	-35°C-60°C, 10%-90% Humidity

KEY FEATURES:

- 1/2.8" Sony Exmor CMOS Sensor
- All Cast Aluminium Material
- Powerful 10x optical zoom
- 16X Digital Zoom
- IR Distance: 80M
- Support ONVIF
- Lens: 5.1-51mm
- IP66 all-environments protection

