


# MOTORBULLET-4MP-W

## 4MP MOTORISED LENS



### Benefits Of Motorised Lens



**Reduce Installation  
Time + Labour**



**Auto Focus Directly  
From DVR**



**No Need For  
Expensive Test  
Monitors**



**No More Fine  
Focusing In  
The Rain**

Image Sensor	1/3" 4.0 megapixels Progressive OV 4689 CMOS
DSP	Hisilicon 3516D
Effective Pixels	2592(H)*1520(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto (1/25 ~ 1/10000s)
Min. Illumination	0.05Lux/F1.2 (Color), 0.01Lux/F1.2(B/W)
Lens	2.8-12mm Motorised Lens
IR Range	Up to 50m
IR Leds	48pcs
S/N Ratio	≥50db(AGC OFF)
Day/Night	Auto(ICR)/Color/B/W
Wdr	>80dB
White Balance	Auto
GAIN CONTROL	Auto
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Compression	H.264/MJPEG/H.265
Resolution	2592*1520/2048*1520/1080P(1920×1080)/ D1(704×576)/VGA(640×480)/QVGA(320×240)
Compression	G.711
Frame Rate	2592*1520(1~15fps)
Main Stream	2048*1520/1080P(1 ~ 25/30fps)
Bit Rate	32KB ~16Mbps, support VBR, CBR
ONVIF	ONVIF V2.4
Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPO, SMTP, UPNP
Max. User Access	8 users, IE, Google, Firefox
Mobile phone	Windows Mobile, iPhone, iPad, Android
Working Temperature	-20 °C~+55 °C , Less than 90% RH
Working Humidity	0% - 90%
IP Rating	IP66
Power Supply	12 VDC ± 10% PoE(802.3af)
Consumption	<3W
Dimension	272mmx87mmx90mm
Weight	1.1 kgs

#### KEY FEATURES:

- 1/3" 4.0 megapixels Progressive OV 4689 CMOS
- 4MP@15FPS
- IR Distance: Up to 50M
- Support ONVIF 2.4
- 2.8-12mm Motorised Lens
- IP66 IP Rating

